


#### **ENERGIZER 13 size**



(top view) (bottom view)

### **Industry Standard Dimensions**

mm (inches)



## **Typical Discharge Characteristics**

**ANSI/IEC Industry Standards / Intermittent Test Protocol** (1.5K ohm 12 hours per day at 21C)



# ZEROMERCURY

#### **Specifications**

**Chemical System:** Zinc Air (Zn/O<sub>2</sub>) **Tab Color:** Orange

ANSI-7000ZD, IEC-PR48 **Designation:** 

**Nominal Voltage:** 1.4 Volts

**Typical Capacity:** 280 mAh (to 0.9 volts)

(Rated at 1.5k ohms at 21°C/50% RH)

**Typical Weight:** 0.8 grams (0.03 oz.)

**Typical Volume:** 0.03 cubic centimeters (0.02 cubic inch)

## **Typical Discharge Characteristics**

**IEC Industry Standards / Standard Test Protocol** (6/2 mA .1S/1H59M 59.9S 12H at 21C)



## **Typical Discharge Characteristics**

IEC Industry Standards / High Drain Test Protocol (12/3 mA .1S/1H59M 59.9S 12H at 21C)



#### **Important Notice**

This data sheet contains typical information specific to products manufactured at the time of its publication. ©Energizer Brands, LLC - Contents herein do not constitute a warranty.

Form No. EBC - 4503H Page 1 of 1